



GENERAL NOTES:

1. PROVIDE STRAIGHT VERTICAL SAW CUTS TO A NEAT LINE AS DIRECTED BY FIELD ENGINEER.
2. CONCRETE SURFACES TO BE CLEANED AND BITUMINOUS TACK OR PRIME COAT APPLIED BEFORE PLACEMENT OF ASPHALTIC TOPPING.
3. CONTRACTOR TO UTILIZE STEEL RUNNING PLATES OR OTHER APPROVED METHODS DURING CURING OF CONCRETE. PLATES TO BE REMOVED UPON SATISFACTION OF FIELD ENGINEER.
4. CONSTRUCTION METHODS AND MATERIALS SHALL BE IN ACCORDANCE WITH GEORGIA D.O.T. STANDARD SPECIFICATIONS FOR CONSTRUCTION OF ROADS AND BRIDGES (LATEST EDITION).

TOWN OF BRASELTON WATER & SEWER DEPARTMENTS

JOB TITLE STANDARD DETAIL	SHEET TITLE PAVEMENT CUT REPAIR DETAIL	DRN. BY: EMI	REV. NO.	BY	DATE
		CKD BY:			
		APPD. BY:			
		DATE: SEP. 2004			
		DETAIL No. S-31	FILE No. 03033\S-31.dwg	SCALE: N.T.S.	