



ACCESS ROAD

PAVEMENT SECTION

NORMAL DUTY

- 2" ASPHALTIC CONCRETE TYPE "E" OR "F" PER GDOT SPECIFICATION
- 6" GRADED AGGREGATE BASE COURSE PER GDOT SPECIFICATION

GENERAL NOTES:

1. COMPACT SUBGRADE TO 95% STANDARD PROCTOR PER ASTM D698.
2. THE SUBGRADE SHALL BE PROOF ROLLED WITH A HEAVY DUMP TRUCK FILLED WITH DIRT (20 TONS MIN.), FULLY LOADED SCRAPER OR A HEAVY RUBBER TIRED ROLLER AS RECOMMENDED BY THE TOWN REPRESENTATIVE. ANY AREAS SHOWING SPONGINESS OR PUMPING SHALL BE EXCAVATED TO REMOVE THE UNSUITABLE MATERIAL, REFILLED WITH SUITABLE MATERIAL, REROLLED AND TESTED.

TOWN OF BRASELTON WATER & SEWER DEPARTMENTS

JOB TITLE STANDARD DETAIL	SHEET TITLE LIFT STATION ACCESS DRIVEWAY	DRN. BY: EMI	REV. NO.	BY	DATE
		CKD BY:	A	EMI	05/22/18
		APPD. BY:			
		DATE: MAY 2005			
		DETAIL No. PS-7	FILE No. 03033\PS-7.dwg	SCALE: N.T.S.	